

Hose couplings with threaded connection and flat seal

Hose couplings type 2VH

Turned hose coupling with swivelling female thread and flat sealing ring of polyurethane (with stainless steel couplings seal of PTFE) type 2VH. The maximum working pressure amounts to 10 bar. This coupling is also fitted on the hose using hose clips (e.g. Type ABA or TORRO).




figure 1




figure 2




figure 3

Hose couplings type 2VH

ERIKS article no.	Hose tail in mm	Thread	Material	Fig.	Weight kg	Order Reference
	13	G 1/2"	ST	1	0,09	2VH 13 ST G1/2"
11057472	13	G 1/2"	SS	1	0,09	2VH 13 SS G1/2"
10038982	13	G 1/2"	MS	1	0,09	2VH 13 MS G1/2"
10038983	13	G 3/4"	MS	1	0,10	2VH 13 MS G3/4"
	19	G 3/4"	ST	1	0,11	2VH 19 ST G3/4"
	19	G 3/4"	SS	1	0,10	2VH 19 SS G3/4"
10038986	19	G 3/4"	MS	1	0,10	2VH 19 MS G3/4"
10038985	19	G 1"	MS	1	0,10	2VH 19 MS G1"
10070284	25	G 1"	SS	1	0,16	2VH 25SS G1"
10038988	25	G 1"	MS	1	0,14	2VH 25MS G1"
10070285	32	G 1 1/4"	SS	1	0,20	2VH 32 SS G1.1/4"
10038989	32	G 1 1/4"	MS	1	0,22	2VH 32 MS G1.1/4"
10070286	32	G 1 1/2"	MS	2	0,31	2VH 32 MS G1.1/2"
10070287	38	G 1 1/2"	SS	1	0,39	2VH 38 SS G1.1/2"
10038990	38	G 1 1/2"	MS	2	0,32	2VH 38 MS G1.1/2"
	38	G 2"	MS	2	0,50	2VH 38 MS G2"
10070288	50	G 2"	SS	1	0,44	2VH 50 SS G2"
10038991	50	G 2"	MS	2	0,47	2VH 50 MS G2"
	50	G 2 1/2"	MS	2	0,72	2VH 50 MS G2.1/2"
	63/65	G 2 1/2"	SS	1	0,82	2VH 63 SS G2.1/2"
10070289	63/65	G 2 1/2"	MS	2	0,83	2VH 63 MS G2.1/2"
10070290	63/65	G 3"	MS	2	1,05	2VH 63 SS G2.1/2"
10070291	75	G 3"	SS	1	0,94	2VH 75 SS G3"
10038992	75	G 3"	MS	2	1,05	2VH 75 MS G3"
	80	G 3"	SS	1	0,91	2VH 80 SS G3"
10070292	80	G 3"	MS	2	1,05	2VH 80 MS G3"
10070293	100	G 4"	MS	3	2,30	2VH 100 MS G4"

G : BSP
 ST : Steel
 SS : Stainless steel 316
 MS : Brass
 AL : Aluminium