







G Y claw coupling



Cast-iron air hose coupling

According to DIN 3483 with oil-resistant sealing ring. Internal lug distance 42 mm for all sizes and designs. As a result it is possible to connect couplings with different connections to each other without using reducing pieces. Also available in brass and stainless steel. Permitted working pressure: 12 bar.

Table of sizes

ERIKS art.no.	Design	Size	Code
		Tailpiece in mm	
		6	SKG 6
10039529		10	SKG 10
10039530		13	SKG 13
10039531		15	SKG 15
10039532		19	SKG 19
10039533		25	SKG 25
			32
		Male thread	
		1/4"	KAG 14
10039492		3/8"	KAG 38
10039493		1/2"	KAG 12
10039494		3/4"	KAG 34
10039475		1"	KAG 10
		1 1/4"	KAG 54
			Female thread
		1/4"	KIG 14
10039489		3/8"	KIG 38
10039490		1/2"	KIG 12
10039491		3/4"	KIG 34
10039474		1"	KIG 10
		1 1/4"	KIG 54
			Material
10039465		Cast iron	VKO
	Blind cap		
		Material	
10037629		NBR	GOER
	Sealing ring		
		Tailpiece in mm	
		10	SSG 10
		13	SSG 13
		15	SSG 15
		19	SSG 19
		25	SSG 25
	Re-adjustable coupling with tailpiece		