

#### GEKA claw coupling









#### GEKA quick-release couplings

Cast brass hose couplings, internal lug distance 40 mm for all sizes and versions.

As a result it is possible to connect couplings with different connections without reducing pieces. As standard the couplings have an NBR sealing ring type 200C.

Maximum working pressure 20 bar.

**Table of sizes**

ERIKS art.no.	Design	Size	Code
		Tailpiece in mm	
10039518		10	100
10039513		13	101
10039523		16	102
10039514		19	103
10039515		25	104
10039516		32	106
10039517		Tailpiece	38
		Male thread	
10039486		3/8"	109A
10039487		1/2"	110A
10039488		3/4"	111A
10039473		1"	113A
10039509		1 1/4"	114A
10039510		1 1/2"	116A
		Female thread	
10039477		3/8"	109
10039471		1/2"	110
10039472		3/4"	111
10039470		1"	113
10039484		1 1/4"	114
10039485		1 1/2"	116
		Material	
10039466		Brass	118
10039467		PVC	118PL
		Material	
10037633		NBR	200 C
10037635		NR	200 D
		FPM	200 V
		Tailpiece in mm	
10039526		13	101 SH
10039527		19	103 SH
10039528		25	104 SH
	Re-adjustable coupling with tailpiece		