



#### RX® CP HiTex 481

##### Application

- CP ducting hose for hot air, smoke and waste gases, vapours, etc. where higher temperatures occur
- hot air blower hose for the preheating of engines
- also for use as folding bellows or compensator

##### Temperature

-60 °C to +600 °C continuous,  
briefly to +700 °C

##### Design

- 2 layers of special impregnated glass fabric, stainless steel-strengthened, exterior with clamping profile in stainless steel

- axially compressible
- flexible and kink-resistant
- robust design
- exterior resistant to friction: the clamping profile precludes the wearing through of the outer foil

##### Couplings

as chosen or to assemble straight on a pipe

##### Assembly method

worm screw clamps type SPIRALEX  
(see page 66-70)

**Data Table**

ERIKS art.no.	Int. diameter	Ext. diameter	Vacuum	Bending radius	Weight	Roll length
	mm	mm	%	mm	kg/m	m
11194386	75	89	29	80	2,18	6
11194387	80	94	25	85	2,44	6
11194388	90	104	18	94	2,58	6
11194389	100	114	15	103	2,58	6
11194390	110	124	13	112	2,49	6
11194391	120	134	11	121	2,70	6
11194392	125	139	10	125	2,81	6
11194403	130	144	9,5	130	2,92	6
11194404	140	154	7,5	139	3,13	6
11194405	150	164	6	148	2,13	6
11194406	160	174	5,5	157	2,26	6
11194408	170	184	5	166	2,40	6
11194409	175	189	5	170	2,46	6
11194410	180	194	4,8	175	2,53	6
11194412	200	214	3,8	193	2,80	6
11194414	215	229	3,5	206	3,01	6
11194416	225	239	3,2	215	3,14	6
11194417	250	264	2,9	238	3,48	6
11194418	275	289	2,4	260	3,82	6
11194419	300	314	1,9	283	4,16	6
11194420	350	364	1,6	328	4,83	6
11194421	400	414	1,3	373	5,51	6
11194422	450	464	1	418	6,12	6
11194453	500	514	0,7	463	6,86	on request
11194454	600	614	0,5	553	8,22	on request
11194455	700	714	0,3	643	9,59	on request
11194456	800	814	0,2	733	10,96	on request
11194457	900	914	0,1	823	12,33	on request
11194458	1.000	1.014	0,1	913	13,70	on request