



RX® MULTIBAR/RAUFILAM

Application

- braided PVC hose for water and air applications, used in all branches of industry
- also for use in the food industry

Temperature

-20 °C to +60 °C

Design

- PVC, transparent with polyester inlays
- internally and externally smooth
- cadmium-free
- bursting pressure = 4 x working pressure
- TÜV tested
- chemical-resistant
- flexible
- food quality: the hose complies with European Directive 90/128/CEE

Couplings

as chosen

Assembly method

ABA, Torro, Norma, Power Clamp

Data Table

ERIKS art.no.	Internal diameter	Wall thickness	Working pressure	Bursting pressure	Bending radius	Roll length
	mm	mm	bar	bar	mm	m
10015709	4	3	23	92	15	50
10015710	6	3	20	80	25	50
10015711	8	3	18	72	30	50
10015712	9	3	16	64	35	50
10015713	10	3	14	56	40	50
10015714	12	3	14	56	55	50
10015715	12	4,2	14	56	50	50
10015716	13	3,3	12	48	70	50
10015717	16	3,7	12	48	90	50
10015718	19	3,7	10	40	130	50
10015707	25	4,3	8	32	200	25
10015708	32	4,8	7	28	310	25
10015705	38	4,8	6	24	420	25
10015706	50	6,5	4	16	620	25

Technical information at 20°C