



RX® MULTIBAR/TX

Application

- braided PVC hose for water and air applications, used in all branches of industry
- also for use in the food industry

Temperature

-20 °C to +60 °C

Design

- PVC, transparent with polyester inlays
- internally and externally smooth
- bursting pressure = 3 x working pressure
- chemical-resistant
- flexible
- food quality: the hose complies with European Directive 90/128/CEE

Couplings

as chosen

Assembly method

ABA, Torro, Norma, Power Clamp

Data Table

ERIKS art.no.	Internal diameter	Wall thickness	Working pressure	Bursting pressure	Bending radius	Weight	Roll length
	mm	mm	bar	bar	mm	kg/m	m
10014825	4	3	18	54	15	0,082	25-50
10014826	5	3	18	54	20	0,093	50
10014827	6	3	18	54	25	0,105	25-50
10014828	8	3	15	45	30	0,128	25-50
10014829	9	3	15	45	35	0,139	25-50
10014830	10	3	15	45	40	0,151	25-50
11194091	12	3	15	45	50	0,175	25
10014839	12,5	3	14	42	55	0,180	50
10014831	13	3,5	12	36	60	0,223	25-50
10014832	15	4	13	39	80	0,264	25-50
10014833	16	3,5	13	39	80	0,264	25-50
10014834	19	4	12	36	100	0,356	25-50
10014729	20	4	10	30	110	0,386	25-50
10014835	25	4,5	9	27	120	0,513	25-50
11190203	30	4	6	18	160	0,52	25-50
10014836	32	5	6	18	180	0,715	25-50
10014837	38	5	5	15	200	0,831	25-50
10014838	50	8	5	15	660	1,792	25

Technical information at 20°C. Also available in various colours on request.