



RX® POLYBAR

Application

- very flexible suction and delivery hose for heavy industrial applications where a higher working pressure is required
- also suitable for liquid food applications

Temperature

-10 °C to +60 °C

Design

- glass-clear PVC, suitable for food, with fully flush steel coil and polyester inlays
- interior and exterior particularly smooth
- very flexible
- food quality: the hose complies with European Directive 90/128/CEE

Couplings

as chosen

Assembly method

ABA, Torro, Norma, Power Clamp

Data Table

ERIKS art.no.	Internal diameter	Wall thickness	Working pressure	Bursting pressure	Vacuum	Bending radius	Weight	Roll length
	mm	mm	bar	bar	%	mm	kg/m	m
11191884	10	4,25	20	60	90	30	0,260	60
11191885	12	4,25	20	60	90	36	0,290	60
11191886	14	4,25	20	60	90	42	0,320	60
11191887	16	4,5	20	60	90	48	0,370	60
11191888	18	4,5	20	60	90	54	0,440	60
11191889	20	4,8	15	45	90	60	0,500	60
11191890	25	5	15	45	90	75	0,650	60
11191891	30	5,5	12	36	90	90	0,770	60
11191892	32	5,5	12	36	90	95	0,850	60
11191913	38	6	12	36	90	110	1,150	30
11191914	40	6	12	36	90	120	1,200	30
11195966	45	6,5	9	27	80	135	1,460	30
11195967	50	6,5	8	24	80	150	1,600	30
11195968	60	7	7	21	80	180	2,020	30
11195969	63	7	7	21	80	192	2,160	30
11195970	70	7,5	6	18	70	210	2,505	30
11195972	76	7,5	6	18	70	228	2,695	30
11196013	80	7,5	6	18	70	240	2,850	20
11196014	90	8	5	15	70	270	3,500	20
11196015	102	8	4	12	70	305	4,040	20

Technical information at 20°C