



RX® POLYFLEX

Application

- flexible pipe for pneumatic lubrication, air or carbon dioxide line in equipment construction
- oil- and petrol-resistant

Design

polyamide (Nylon), PA12

Couplings

rectupush insert couplings
(see page 60-65)

Temperature

-60 °C to +100 °C

Data Table

ERIKS art.no.	Int. diameter mm	Ext. diameter mm	Colour	Working pressure bar	Bending radius mm	Roll length m
10014841	2	4	White	44	20	100
10069598	2	4	Red	44	20	100
10069597	2	4	Green	44	20	100
10069596	2	4	Yellow	44	20	100
10069595	2	4	Blue	44	20	100
10069604	3	5	Black	33	25	100
10014842	3	5	White	33	25	100
10069603	3	5	Red	33	25	100
10069602	3	5	Green	33	25	100
10069601	3	5	Yellow	33	25	100
10069600	3	5	Blue	33	40	100
10014853	4	6	Black	26	30	100
10014843	4	6	White	26	30	100
10069608	4	6	Red	26	30	100
10069607	4	6	Green	26	30	100
10069606	4	6	Yellow	26	30	100
10069605	4	6	Blue	26	30	100
10014854	6	8	Black	19	50	100
10014844	6	8	White	19	50	100
10069612	6	8	Red	19	50	100
10069611	6	8	Green	19	50	100
10069610	6	8	Yellow	19	50	100
10014846	6	8	Blue	19	50	100
10014855	8	10	Black	14	60	50
10014845	8	10	White	14	60	50
10014851	8	10	White	14	60	50
10069615	8	10	Red	14	60	50
10069614	8	10	Green	14	60	50
10069613	8	10	Yellow	14	60	50
10014847	8	10	Blue	14	60	50
10015732	10	12	Black	12	70	50
10014852	10	12	White	12	70	50
10069618	10	12	Red	12	70	50
10069617	10	12	Green	12	70	50
10069616	10	12	Yellow	12	70	50
10014848	10	12	Blue	12	70	50
10015730	11	14	White	16	80	50

Technical information at 20°C