



#### RX® POLYROS/GK

##### Application

Clear PVC hose for feeding of liquids and gases in all industrial applications where the observation of the medium in the hose is a necessity

##### Temperature

-20 °C to +60 °C

##### Design

- PVC, transparent
- internally and externally smooth
- chemical-resistant
- food quality: the hose complies with European Directive 90/128/CEE

##### Couplings

as chosen

##### Assembly method

ABA, Torro, Ear clamps

**Data Table**

ERIKS art.no	Int. diameter mm	Wall thickness mm	Working pressure bar	Roll length m
10014878	3	1,5	5	100
10014879	4	1,5	4	100
10014880	5	1,5	3	100
10014881	5	2	4	100
10014882	6	1	2	100
10014883	6	1,5	3	100
10014884	6	2	4	50
10014885	7	1	2	100
10014886	7	1,5	3	50
10014887	8	1	2	100
10014888	8	2	3	50
10014889	8	3	4	50
10014890	9	1,5	2	50
10014891	9	2	3	50
10014892	10	2	3	50
10014893	10	3	3	50
10014894	12	2	2	50
10014895	12	3	3	50
10014896	13	2	2	50
10014897	13	3	3	50
10014898	14	2	2	50
10014899	15	3	3	50
10014900	16	2	2	50
10014901	16	3	2	50
10014902	19	2,5	2	50
10014903	20	3	2	50
10014904	22	3	2	50
10014905	25	3	2	50
10014906	25	4	2	50
10014907	30	5	2	50
10014908	32	5	2	50
10014909	35	5	2	50
10014910	38	5	2	50
10014911	40	5	2	50
10014912	50	5	1	50

Technical information at 20°C