



RX® POLYROS/RAUCLAIR

Application

Clear PVC hose for feeding of liquids and gases in all industrial applications where the observation of the medium in the hose is a necessity

Temperature

-20 °C to +60 °C

Design

- PVC, transparent
- internally and externally smooth

- flexible

- chemical-resistant
- cadmium-free
- suitable for foodstuffs according to BGA

Couplings

as chosen

Assembly method

ABA, Torro, Ear clamps

Data Table

ERIKS art.no	Int. diameter mm	Wall thickness mm	Working pressure bar	Roll length m
10015766	2	1	5,9	100
10015767	3	1,5	5,3	100
10015768	4	1	3,2	100
10015769	4	1,5	4,3	100
10015770	4	2	5,3	100
11096033	5	1	3	100
10015771	5	1,5	3,6	100
10015772	6	1	2,2	100
10015773	6	1,5	3,2	100
10015774	6	2	4	100
10015775	7	1,5	2,8	100
10015748	8	2	3,2	50
10015749	9	1,5	2,2	50
10015750	9	2	2,9	50
10015751	10	1,5	2	50
10015752	10	2	2,6	50
10015753	10	3	3,6	50
10015754	12	2	2,2	50
10015755	12	3	3,2	50
10015756	13	3	3	50
10015757	14	2	2	50
10015758	15	2	1,8	50
10015759	16	2	1,7	50
10015760	16	3	2,5	50
10015761	18	3	2,2	50
10015762	19	3,5	2,4	50
10015763	20	3	2	50
10015764	25	3	1,7	50
10015765	25	4	2,2	50
10015742	30	5	2,2	25
10015743	32	5	2,1	25
10015744	38	5	1,8	25
10015745	40	5	1,7	25
10015746	50	5	1,4	25
10015747	60	5	1,2	25

Technical information at 20°C