

RX® SPIRALEX-TER



Design

- special worm screw clamp for coiled hoses type Vacufixx, Abraflex and CP (with the exception of the hose types Abraflex-HD and Abraflex-SHD)
- specially designed to prevent electrical charging in a certain and professional way without releasing the coil; no risk of damaging the hose!
- supplied with earthing screw on the coiled bridge; an earth cable can optionally be supplied
- worm screw clamp with integrated “coiled bridge”, so complete sealing of the whole circumference of the hose is guaranteed

- this guarantees the certain and tight connection of the hose to the connecting piece
- simple to assemble
- according to DIN 3017

Material

- band chrome steel
- coiled bridge stainless steel
- screw galvanised steel
- earthing screw stainless steel

Data Table

ERIKS art.no.	Front internal hose diameter	Band width
	mm	mm
11195181	38 – 45	9
11195196	50 – 55	9
11195197	60 – 65	9
11195199	70 – 75	9
11195200	80	9
11195201	90	9
11195202	100 – 102	9
11195223	110 – 115	9
11195224	120 – 127	9
11195225	130	9
11195226	140	9
11195227	150 – 152	9
11195229	160	9
11195230	170 – 175	9
11195231	180	9
11195232	190	9
11195244	200	12
11195245	215	12
11195247	225	12
11195248	250	12
11195249	275	12
11195250	280	12
11195251	300	12
11195252	315 – 325	12
11195253	350	12
11195255	380	312
11195256	400	312
11195257	450	12
11195258	500	12

Larger sizes for hoses to diameter 1,000 mm, available on request.