



### RX®-CLEANFIXX FDA

#### Application:

- Flexible and strong hot water and steam hose. Suitable for cleaning floors in abattoirs and food industry.
- The hose does not leave any marks.

#### Temperature range :

For water: -40 °C to +95 °C  
For steam: up to 164 °C

#### Bursting pressure :

60 bar

#### Internal wall:

- White, smooth, homogeneous and seamless extruded EPDM rubber
- Resistant to most common cleaning agents
- Temperature resistant to +95 °C continuous for water, and +164 °C with low pressure steam
- FDA quality

#### Inlays :

- Wound textile inlays
- Strong and resistant to distortion

#### Outside wall :

- EPDM rubber, blue
- Smooth with sleeve print
- Durable and age resistant
- Resistant to traces of animal fats and vegetable oils

#### Markings :

White marking with text:  
"RX CLEANFIXX FDA STEAM OPEN SYSTEM 6 BAR 164 °C "

#### Connections :

DIN 11851, DIN 11864, SMS, Tri-clamp, ERITITE, TW, flanges, ...

#### Assembly :

Clamps, ERIKS 2-part hose clamp, Band-it, hydraulic compression sleeve, Lactafix (bacteria-free)

#### Additional information:

This hose is ADI-free  
(Animal Derived Ingredient Free).

#### Pressure hose without spiral winding

ERIKS art.no.	Internal diameter	Wall thickness	Working Pressure	Vacuüm	Bending radius	Weigh	Roll length
	mm	mm	bar	%	mm	kg/m	m
10069593	10	5	6	20	75	0.27	40
11089003	13	5	6	20	100	0.34	40
11241415	16	6	6	20	120	0.51	40
11089004	19	6	6	20	160	0.60	40
11089005	25	7	6	20	200	0.89	40
11089006	32	7	6	20	260	1.10	40
11089007	38	8	6	20	300	1.65	40
11089008	50	10	6	20	380	2.35	40

Stock articles can also be obtained per meter length.