



RX®-DELIFIXX-LITE

Application :

- Premium beer hose for transport of beer, wine, alcoholic (max. 40%), and non-alcoholic drinks, fruit juices, ...
- Also suitable for oily and fatty foodstuff (fats concentration max 40%)
- High performance (mechanical and thermal stress) under the harshest cleaning conditions.
- Odourless and tasteless inner liner to guarantee that the conveyed medium remains absolutely unchanged.
- Special corrugation of the outer cover allows utmost flexibility and exceptional easy to handle.

Temperature range :

-30 °C to +90 °C continuous
can be steamed at 130 °C / 30 minutes

Bursting pressure : 45 bar

Internal wall :

- Smooth, mirror-like, light colour CR/NR based rubber
- Odour and tasteless
- Resistant to the harshest cleaning agents and trouble-free CIP (also see page 23)
- Oil and fat resistant. (max 40%)
- Complies with the FDA standards, with the German "Technische Universitaet Muenchen WEIHENSTEPHAN" and conforming to the M.D. 21/03/73 and following amendments.
- Animal Ingredients Free (ADI-free)

Inlays :

Plies of synthetic cord and embedded steel wire helix

Outside wall :

- Sparkling red EPDM based rubber
- Wide corrugation with cloth finish
- Durable, abrasion, weather and age resistant

Markings :

- Blue marking with text:
"RX DELIFIXX-LITE BEER/WINE 15 BAR SD"

Connections :

DIN 11851, DIN 11864, SMS,RJT, Tri-clamp, ERITITE, TW, flanges, ...

Assembly :

Clamps, ERIKS 2-part hose clamp, crimping ferules

Notes :

- For cleaning new and used hoses, see page 23
- Rubber rings for protecting the floor and couplings are recommended.

Vacuum and pressure hose with spiral winding

ERIKS art.no.	Internal diameter	Wall thickness	Working Pressure	Vacuüm	Bending radius	Weigh	Roll length
	mm	mm	bar	%	mm	kg/m	m
11549642	32	7	15	90	90	1.30	40
11549653	38	7	15	90	120	1.42	40
11549654	51	7,5	15	90	150	1.85	40
11549655	63,5	8	15	90	220	2.50	40
11549656	76	9	15	90	260	3.70	40
11549657	102	9	15	90	400	4,60	40

Stock articles can also be obtained per meter length.