



#### RX®-EXCELLENT WHITE In accordance with EN 12115

##### Application:

- The most universal vacuum and pressure hose with mirror smooth PFA internal wall for pharmaceutical, cosmetics, foodstuffs and chemical industry.
- Rigid and non-kink.
- Easy to handle due to smooth outside wall.

##### Temperature range :

- -40 °C to +130 °C continuous
- Can be steamed/disinfected internally and externally up to 150° for max. 30 minutes

##### Bursting pressure :

> 40 bar

##### Internal wall:

- White, food resistant PFA compliant with USP VI and FDA title 21P.177.1550
- Smooth, homogeneous and seamless

##### Inlays :

- Textile
- Completely enclosed steel winding
- 2 conductive wires

##### Outside wall :

- Specially patented electrically conductive outside wall ( $R < 10^6 \Omega$ )
- Complies with FDA 21P.177 2600
- Very low friction when dragged over concrete floors
- Smooth, dirt-resistant
- Chemically resistant
- Ozone and weather resistant

##### Markings :

Red/white/blue:

RX® - Excellent White USP VI FDA SD 10 Bar M USP Class VI

##### Connections :

All clamp unit connections in accordance with EN 14420 (screw thread, flange, Tri-clamp, DIN11851, DIN11864, etc.)

##### Assembly :

Clamps and compression sleeves

##### Additional information:

This hose is ADI-free (Animal Derived Ingredient Free).

#### Pressure hose with spiral winding

ERIKS art.no.	Internal diameter	Wall thickness	Working Pressure	Vacuüm	Bending radius	Weigh	Roll length
	mm	mm	bar	%	mm	kg/m	m
11384124	13	6.0	10	90	60	0.55	20
11384125	19	6.0	10	90	90	0.72	20
11384126	25	6.0	10	90	140	0.89	20
11384127	32	6.5	10	90	200	1.16	20
11384128	38	6.5	10	90	250	1.47	20
11384129	51	7.25	10	90	300	2.08	20
11384130	63.5	8.0	10	90	380	2.80	20
11384131	76	8.0	10	90	500	3.48	20

Stock articles can also be obtained per meter length.

