



RX®-LABO SILICONE FDA

Application :

For the un-pressurised transport of weak acids and alkalis, alcohol, ...

Temperature range :

-55 °C to +200 °C continuous

Internal wall :

Silicone, semi-transparent
Hardness : 60° shore

Inlays : None

Outside wall :

Silicone, semi-transparent
Hardness : 50° shore

Markings : None

Connections : As required

Assembly :

ABA, Torro, compression sleeves.

Note :

- Also available in colour
- For pressure applications: see type RX-SILIPRESS ROOD

Pressure hose without spiral winding

ERIKS art.no.	Int. diameter	Wall thickness	Weight kg/m	Roll length m
	mm	mm		
10015798	1	1	0.01	50
10015799	2	1	0.01	50
10015800	2	1.5	0.02	50
10015801	2	2	0.03	50
10015802	3	0.5	0.02	50
10015803	3	1	0.03	50
11035942	3	2	0.05	50
10015804	4	1	0.02	50
10015805	4	1.5	0.03	50
10015806	4	2	0.05	50
11014806	5	0.5	0.01	50
10015807	5	1.5	0.04	50
10015808	5	2	0.05	50
10015909	5	3	0.09	50
10015810	6	1	0.03	50
10015811	6	1.5	0.04	50
10015812	6	2	0.06	50
10015228	6	3	0.10	50
10015813	7	1	0.04	50
10015814	7	1.5	0.05	50
11008033	7	3	0.09	50
10015815	8	1	0.05	50
10015816	8	2	0.07	50
10015817	9	2	0.08	50
10015229	10	2	0.09	50
10015818	10	2.5	0.12	50
10015819	10	3	0.15	50
11024567	10	4	0.20	50
10015795	12	3	0.17	25
10069647	15	1.5	0.14	25
10015796	15	3	0.20	25
10015797	19	3	0.26	25
10015794	25.4	3.2	0.34	15

Technical data at 20 °C. Stock articles can also be obtained per meter length.