



RX®-PURIFIXX

Application:

- Universal "high purity" hose with smooth PFA internal wall for the transport of pharmaceutical, cosmetics, food and chemical products.
- Rigid and non-kink.
- Very easy to handle
- Recommended for "high purity" conditions.
- Can be sterilised in autoclave

Temperature range :

- -30 °C to +150 °C

Bursting pressure :

- > 40 bar

Internal wall:

- White, food resistant PFA compliant with USP IV and FDA title 21 P. 177.1550.
- Smooth, homogeneous and seamless
- Odour and tasteless

Inlays :

- Synthetic inlays
- Completely enclosed steel winding
- 2 conductive wires

Outside wall :

- Silicone, smooth and FDA guideline compliant
- Can be sterilised in autoclave
- Easy to clean with detergents
- Standard colour is white, other colours available on request

Markings :

RX®-PURIFIXX USP VI FDA ADI-free SD 10 bar

Connections:

All clamp unit connections in accordance with EN 14420 (screw thread, flange, Tri-clamp, DIN11851, DIN11864, etc.)

Assembly :

Clamps and compression sleeves

Additional information:

This hose is ADI-free (Animal Derived Ingredient Free).

Vacuum and pressure hose with spiral winding

ERIKS art.no.	Internal diameter	Wall thickness	Working Pressure	Vacuüm	Bending radius	Weigh	Roll length
	mm	mm	bar	%	mm	kg/m	m
	13	7,5	10	90	45	0,69	20-22
	16	7,5	10	90	55	0,78	20-22
	19	7,5	10	90	65	0,88	20-22
	25	7,5	10	90	85	0,91	20-22
	32	8,0	10	90	120	1,34	20-22
	38	8,0	10	90	140	1,63	20-22
	51	8,5	10	90	180	2,39	20-22

Stock articles can also be obtained per meter length.