



Material Data Sheet, October 2005

## TECANAT GF 30

Chemical Designation :

DIN-Abbreviation:

Colours, fillers:

Polycarbonate

PC GF 30

30% glasfibers

### Main features

- | good heat deformation resistance
- | good electrical insulation
- | sensitive to stress cracking

rigid  
easily welded and bonded

### Preferred Fields

- | mechanical engineering
- | transport and conveyor technology
- | packaging and paper processing machinery
- | precision engineering

- | automotive engineering
- | textile machinery
- | electrical engineering
- | electrical tools

### Applications

Diverse machine parts, housing parts, insulators, plugs, settings, support rings, wiper blades

### Properties

#### Mechanical

Tensile strength at yield

dry / moist

MPa

standard

Elongation at yield

%

Tensile strength at break

130

MPa

DIN EN ISO 527

Elongation at break

2,5

%

DIN EN ISO 527

Modulus of elasticity in tension 7500 MPa DIN EN ISO 527

Modulus of elasticity after flexural test MPa

Hardness 148 ISO 2039/1 (Kugeldruck-Härte, 358N)

Impact strength 23° C (Charpy) 55 DIN EN ISO 179 (Charpy)

Creep rupture strength >50 MPa after 1000 h with static load

Time yield limit for 1% elongation after 1000 h MPa

Co-efficient of friction  
 $p = 0,05 \text{ N/mm}^2 v = 0,6 \text{ m/s}$   
on steel, hardened and ground

Wear  $\mu\text{m/km}$   
 $p = 0,05 \text{ N/mm}^2 v = 0,6 \text{ m/s}$   
on steel, hardened and ground

---

Thermal	dry / moist	standard
---------	-------------	----------

---

Crystalline melting point °C

Glass transition temperature 148 °C DIN 53 765

Heat distortion temperature 142 °C ISO-R 75 Verfahren A (DIN 53 461)  
HDT, Method A

Heat distortion temperature 142 °C HDT, Method B

Max. service temperature  
short term 140 °C

long term 120 °C

Thermal conductivity (23° C) 0,26 W/(K·m)

Specific heat (23° C) J/g.K

Coefficient of thermal expansion (23–55°C) 3  $10^{-5} \text{ 1/K}$  DIN 53 752

---

## Properties

### Electrical

	dry / moist	standard
Dielectric constant ( $10^6$ Hz)	3,3	DIN 53 483, IEC-250
Dielectric loss factor ( $10^6$ Hz)	0,009	DIN 53 483, IEC-250
Specific volume resistance	$10^{16}$	$\Omega \cdot \text{cm}$
Surface resistance	$10^{14}$	$\Omega$
Dielectric strength	30	kV/mm
Resistance to tracking	KB 160	DIN 53 480, VDE 0303 Teil 1

### Miscellaneous

	dry / moist	standard
Density	1,42	$\text{g/cm}^3$
Moisture absorption (23°C/50RH)	0,1	%
Water absorption to equilibrium	0,28	%
Flammability acc. to UL standard 94	HB	DIN EN ISO 62

(1) Testing of semi-finished products

The above information corresponds with our current knowledge and indicates our products and possible applications. We cannot give a legally binding guarantee of chemical resistance, of certain properties and the suitability of our products and their applications. Our products are not destined for use in medical and dental implants. Existing commercial patents must be observed. Unless otherwise stated, these values represent averages taken from injection moulding samples, dry as moulded. We reserve the right to make technical alterations.